


NOTICE OF PROPRIETARY RIGHTS:THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO Somefly technology Co.,Ltd.
IT MUST NOT BE REPRODUCED OR DISCLOSED TO OTHERS OR USED IN ANY OTHER WAY, IN WHOLE OR PART EXCEPT AS AUTHORIZED
IN WRITING BY Somefly technology Co.,Ltd.

RoHS compliant

SYM	REVISION	DESCRIPTION	DFTM	DATE	APPD	APPD



NOTES:
1. MATERIALS AND FINISHES:
BODY - BRASS, WHITE BRONZE PLATING
INNER CONTACT - BRONZE, SILVER PLATING
INSULATOR - PTFE
2. ELECTRICAL:
A. IMPEDANCE: 50 OHM
B. FREQUENCY RANGE: DC - 6 GHz
C. VSWR: 1.25MAX.@3GHz, 1.35 MAX.@6GHz
D. INSERTION LOSS: 0.05XSQRT[F(GHz)]dB MAX.
E. VOLTAGE RATING: 500 VRMS
F. DIELECTRIC WITHSTANDING VOLTAGE: 2000 VRMS MIN.
G. INSULATION RESISTANCE: 5000 MΩ MIN.
H. INTERMODULATION 3RD ORDER: -135 dBc MAX. (2 X 43 dBm)

3. MECHANICAL:
A. DURABILITY: 100 CYCLES MIN.
B. TEMPERATURE RANGE: -40℃ TO +125℃
4. PACKAGING:
A. QUANTITY: PACK 100PCS
B. MARKING: TRAY TO BE MARKED ""

CUSTOMER OUTLINE DRAWING
ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

MATL:		UNLESS OTHERWISE SPECIFIED				DFTM: TaoYang		Somefly technology Co.,Ltd			
		ALL DIMENSIONS ARE IN mm MACHINED SURFACES FINISH 1.6RMS MAX. REMOVE ALL BURRS 0.15×45°MAX. BREAK MACHINE CORNERS 0.15×45°D MAX. FILLET R. TOLERANCES ON DECIMALS .X ±0.2 .XX ±0.1 ANGLES±2° FRACTIONS±N/A				DATE: 2022.05.12					
						CHKD HeTong		N Female To SMA Female Adaptor			
						DATE: 2022.05.12					
USED ON:						APPD: Stone					
SCALE: 2/1	DWG SIZE A4	DO NOT SCALE DRAWING		SURFACE (mm ²) XX .XX		WEIGHT (g) XX .XX		DATE: 2022.05.12	SHT	064-A600P-BS	REV A.0