


NOTICE OF PROPRIETARY RIGHTS: THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO Somefly technology Co.,Ltd.
IT MUST NOT BE REPRODUCED OR DISCLOSED TO OTHERS OR USED IN ANY OTHER WAY, IN WHOLE OR PART EXCEPT AS AUTHORIZED
IN WRITING BY Somefly technology Co.,Ltd.

RoHS compliant

SYM	REVISION	DESCRIPTION	DFTM	DATE	APPD	APPD



NOTES:

1. MATERIALS AND FINISHES:

BODY - BRASS, WHITE BRONZE PLATING
OUTER CONTACT - BRASS, WHITE BRONZE PLATING
INNER CONTACT - BERYLLIUM, SILVER PLATING
INSULATOR - PTFE

2. ELECTRICAL:

A. IMPEDANCE: 50 OHM
B. FREQUENCY RANGE: DC - 6 GHz
C. VSWR: 1.25 MAX. @ DC - 3 GHz
D. INSERTION LOSS: $0.05X\sqrt{F(GHz)}$ dB MAX.
E. VOLTAGE RATING: 500 VRMS
F. DIELECTRIC WITHSTANDING VOLTAGE: 2000 VRMS MIN.
G. INSULATION RESISTANCE: 5000 MΩ MIN.
H. INTERMODULATION 3RD ORDER: -140 dBc MAX. (2 X 43 dBm)

3. MECHANICAL:

A. DURABILITY: 100 CYCLES MIN.
B. TEMPERATURE RANGE: -40°C TO +125°C
C. COMPATIBLE WITH STANDARD: IEC61169-15

CUSTOMER OUTLINE DRAWING
ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

MATL:		UNLESS OTHERWISE SPECIFIED				DFTM: 006		Somefly technology Co.,Ltd									
		ALL DIMENSIONS ARE IN mm MACHINED SURFACES FINISH 1.6RMS MAX. REMOVE ALL BURRS 0.15x 45°MAX. BREAK MACHINE CORNERS 0.15x 45°D MAX. FILLET R. TOLERANCES ON DECIMALS .X ±0.2 .XX ±0.1 ANGLES±2° FRACTIONS±N/A				DATE: 2022.05.18											
						CHKD HeTong		SMA Female for 1/4 Cable Connector									
						DATE: 2022.05.18											
USED ON:						APPD: Stone											
SCALE: 4/1		DWG SIZE A4		DO NOT SCALE DRAWING		SURFACE (mm²) XX		WEIGHT (g) XX		DATE: 2022.05.18		SHT		096-23H0M-BSC		REV	A.0